

## GB 11 AJ



### Features:

Grain:	Aluminum oxide
Backing:	J-cloth
Bonding:	Artificial Resin
Coating:	Closed
Additions:	Top-Size coating
Grit Range:	<b>60, 80, 100, 120, 150, 180, 220, 240, 280, 320, 400*</b> ,
Appearance:	Neutral

\* ■ = in stock

■ = available within 3-5 weeks

### Benefits:

- Cool finish thanks to the top-size coating
- Very flexible backing adapts perfectly to the workpiece contour
- Versatile use on stainless steel, steel, titanium, brass and wood
- Wide grain range
- Easy to tear off by hand
- Neutral backing

### Applications:

- To be used in dry grinding
- Ideal for low-alloy steel, stainless steel, brass, copper and non-ferrous metals
- Flexible structure is optimal for surgical instruments, cutlery and relevant industries
- Grinding of heavily contoured parts, such as turbine blades, robot grinding cells for fittings and door handles
- High-performance profile grinding of hard wood and furniture edges

Application example:



For the right cutting speed for your application, please refer to the cutting speed information sheet.

### GeBrax GmbH

Obere Hommeswiese 41-45  
57258 Freudenberg  
Germany

Phone: +49 27 34 / 28 474-0  
Fax: +49 27 34 / 28 474-10

E-Mail: [info@gebrax.de](mailto:info@gebrax.de)  
[www.gebrax-abrasives.com](http://www.gebrax-abrasives.com)

Further information on request. Subject to technical changes.

### Materials:

